

ANTI-VIBRATION FLOOR SUPPORT KIT



Kit composition

- 2 anti-vibration floor support
- 2 aluminium profiles 41x41
- 4 screws for profile M10 x 40 (except length 250, it has 2)
- 4 bubble level

Measures

- 250 x 163 x 98..... Ref. 8109250169
- 450 x 163 x 98..... Ref. 8109450169
- 600 x 163 x 98..... Ref. 8109600169
- 1000 x 163 x 98..... Ref. 8109100169
- 500 x 130 x 60..... Ref. 8109500136
- 400 x 130 x 95..... Ref. 8109400139
- 600 x 130 x 95..... Ref. 8109600139

Table of maximum loads

- 250 x 163 x 98..... 280Kg
- 450 x 163 x 98..... 480Kg
- 600 x 163 x 98..... 680Kg
- 1000 x 163 x 98..... 980Kg
- 500 x 130 x 60..... 420Kg
- 400 x 130 x 95..... 255Kg
- 600 x 130 x 95..... 450Kg

Technical data

- Floor support manufactured with vulcanization of rubber compounds and natural rubber.
- The hardness of the rubber is SHORE 52-55HA
- Aluminium profile of 41 x 21mm.
- Level bubbles in PVC capsules with tinted water for correct positioning on the ground.
- Screws with galvanized anticorrosive surface treatment.
- Working temperature: from -40 ° C to + 80 ° C.
- Resistant to UVA rays.
 1. Lamp type UVA340
 2. Irradiation intensity of 0,76W/m2
 3. Cycle mode: 8h of light, 4h of condensation
 4. Test temperature: 60°C light and 50°C condensation.
 5. Test time: 72h
 6. Test equipment: UV aging test AGC-RE-E151
 7. Final result: slightly yellowish appearance, no damage visible.





MARTIGRAP

Pol. Ind. Gelidense III – Naves 20-21B

08790 Gelida – Barcelona – Spain

Tel. +34 93 779 35 21

E-mail: export@grupohea.es

www.martigrap.com

Applications

- Especially suitable for installation or support of air conditioning and aerothermal groups.
- Facilitates the placement and support of pipes on flat roofs.

Advantages

- Floor support that, due to its construction, provides great stability.
- It adapts to all types of air conditioning and aerothermal groups.
- High load capacity (see table maximum loads).

