

PSH 80/120/150/200 WE-L/R VERTICAL and WE-H HORIZONTAL

The main features

High energy efficiency thanks to minimal standby energy losses

Heat exchanger connection and electric heating element for individual DHW convenience

Durable, low-scaling stainless steel heating element

Temperature curve display on the outer jacket

Variable temperature selection from 5 - 80 °C for high level of convenience

Easy to transport and install with ergonomic recessed grips on the appliance

Universal wall mounting bracket for quick and easy installation

DHW circulation connection increases DHW convenience in longer pipe networks





Type	PSH 80 WE-H	PSH 120 WE-H	PSH 150 WE-H
Code	430150	430150	430150
Rated capacity	79 l	120 l	151 l
Height			
Diameter	510 mm	510 mm	510 mm
Technical data			
Connected load with ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	1,04 kWh	1,41 kWh	1,81 kWh
Energy efficiency class	C	C	C
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	42,2 kg	54,1 kg	61,2 kg



Type	PSH 200 WE-H	PSH 80 WE-L	PSH 120 WE-L
Code	430150	430080	430080
Rated capacity	191 l	79 l	120 l
Height		871 mm	1178 mm
Diameter	510 mm	510 mm	510 mm

Technical data

Connected load with ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	1,67 kWh	0,93 kWh	1,17 kWh
Energy efficiency class	C	B	B
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	72,5 kg	37,2 kg	48,1 kg



Type	PSH 150 WE-L	PSH 200 WE-L	PSH 80 WE-R
Code	430080	430080	430080
Rated capacity	151 l	191 l	79 l
Height	1410 mm	1715 mm	871 mm
Diameter	510 mm	510 mm	510 mm

Technical data

Connected load with ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	1,49 kWh	1,71 kWh	0,93 kWh
Energy efficiency class	C	C	B
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	55,2 kg	65,3 kg	37,2 kg



Type	PSH 120 WE-R	PSH 150 WE-R	PSH 200 WE-R
Code	430080	430080	430080
Rated capacity	120 l	151 l	191 l
Height	1178 mm	1410 mm	1715 mm
Diameter	510 mm	510 mm	510 mm

Technical data

Connected load with ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	1,17 kWh	1,49 kWh	1,71 kWh
Energy efficiency class	B	C	C
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	48,1 kg	55,2 kg	65,3 kg

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.